PROLINE STACKABLE PLASTIC PIPE STANDS PIPE EQUIPMENT INC.

Proline pipe stands are presently being used successfully for pipeline construction jobs in conjunction with wooden skids for their convenience, economy and ease of handling. These stands have been thoroughly tested and have maximum working load capacities (under ideal conditions) for each model listed below.



Proline pipe stands come in three convenient sizes. 2"to 8", 8" to 12" and 12" to 24". The advantages of these pipe stands over wooden skids are their lightweight, ease in handling, transportation, and storage. One plastic stand will replace several wooden skids and one hundred 2-8" pipe stands will fit on a standard 4-foot by 4-foot pallet.

Company names can be engraved or stamped on the stand for inventory control or identification concerns. The saddles are contoured for greater support and for protection of pipe coatings, and each pipe stand is built tough, to withstand the conditions encountered in pipeline construction.

The product is an UV stabilized HDPE (High Density Polyethylene) with an approximate UV life span of 6.5 years. The polyethylene has a melting point of 125° C (257° F) and a low temperature impact resistance of 40° F below (- 40° C). Pigments can be added to produce many different colours if desired. Maximum ambient temperature limit is 98° F (37° C).

The stands are completely recyclable at the end of their useable life and older stands can be tested at different intervals to be culled from old stock if required. Custom sizes are available upon request.

2"- 8" Proline Plastic Pipe Stands	8"-12" Proline Plastic Pipe Stands	<u>12"- 24" Proline Plastic Pipe Stands</u>
Yellow Cone Shape	Yellow Cone Shape	Yellow Multi-angled Shape
Overall Height: 21" (53.34 cm)	Overall Height: 24" (60.96 cm)	Overall Height: 26" (66.04 cm)
Saddle Height: 19" (48.26 cm)	Saddle Height: 22" (55.88 cm)	Saddle Height: 20.5" (52.07 cm)
Base Diameter: 23.5" (59.69 cm)	Base Diameter: 25.5" (64.77 cm)	Base Diameter: 41.0" (104.14 cm)
Weight: 10 lbs. (4.54 Kgs.)	Weight: 18 lbs. (8.17 Kgs.)	Weight: 42 lbs. (19 Kgs.)
Thickness: 0.2185" (.5549 cm)	Thickness: 0.3125" (.7938 cm)	Thickness: 0.3937" (1.000 cm)
Maximum Load: 1980 lbs. (898 kgs)	Maximum Load: 3475 lbs. (1576 kgs)	Max Load:: 10000 lbs. (4540 kgs)
No. Per Standard Pallet: 100	No. Per Standard Pallet: 50	No. Per Standard Pallet: 15



A *High Temperature* WHITE pipe stand is available in all the sizes above and is recommended for environments where ambient temperatures can reach beyond the yellow pipe stand's maximum temperature rating of 98°F (37°C).

Maximum low temperature is 40°F below (- 40°C). Maximum high temperature for this pipe stand is 113°F (45°C). The white colour, along with more HDPE material added at the time of manufacturing, makes for higher heat resistant product for only a slightly higher price.

Discounts are available on Yellow & White PPS when 100, 500 and 1000+ are ordered and shipped together.

PROLINE PIPE EQUIPMENT INC.

7141 – 67 STREET EDMONTON, ALBERTA, CANADA T6B 3L7 TELEPHONE: 780-465-6161 FAX: 780-466-3036 sales@proline-global.com www.proline-global.com